



# Wall mounted unit

FTXP-N + RXP-N

comfora

DAIKIN



Onecta app



Energy saving during  
standby mode



3-D air flow



Practically inaudible

Discreet wall mounted unit providing high efficiency and comfort

- › Onecta app
- › Practically inaudible
- › Voice control
- › Silver allergen removal and air purifying filter
- › 3-D airflow: air is blown into all corners of a room
- › Ideal for above door installation

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

# FTXP-N + RXP-N



Indoor unit				FTXP	20N	25N	35N	50N	60N	71N		
Dimensions	Unit	HeightxWidthxDepth	mm		286 x770 x225			295 x990 x263				
Weight	Unit		kg	8.50			9.00		13.5			
Air filter	Type	Removable / washable										
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m³/min	4.2 / 5.6 / 7.4 / 9.5	4.2 / 5.8 / 7.7 / 9.7	4.5 / 6.3 / 8.3 / 11.5	8.3 / 11.5 / 14.0 / 16.3		9.2 / 11.8 / 14.4 / 16.8	10.1 / 11.8 / 14.4 / 16.8	
		Heating	Silent operation / Low / Medium / High	m³/min	5.2 / 6.2 / 8.1 / 10.4	5.2 / 6.4 / 8.1 / 10.4	5.3 / 7.0 / 9.0 / 11.5	10.4 / 11.8 / 14.4 / 17.3		11.0 / 12.4 / 15.3 / 17.9		
Sound power level	Cooling			dBA	55		58		59		60	62
	Heating			dBA	55		58		61		62	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	19 / 25 / 39	19 / 26 / 40	20 / 27 / 43		27 / 34 / 43		30 / 36 / 45	
	Heating	Silent operation/Low/High		dBA	21 / 28 / 39	21 / 28 / 40	21 / 29 / 40		30 / 33 / 42		32 / 35 / 44	
Control systems	Infrared remote control				ARC480A78			ARC480A53				
	Wired remote control				BRC944B2 / BRC073A1			-				

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | See separate drawing for electrical data


Outdoor unit				RXP	20N	25N	35N	50N	60N	71N		
Dimensions	Unit	HeightxWidthxDepth	mm		556 x740 x343			734 x954 x401				
Weight	Unit		kg	24			46		50			
Sound power level	Cooling			dBA	-							
Sound pressure level	Cooling	Nom./High		dBA	-46		-48		47 / -		49 / -	52 / -
	Heating	Nom./High		dBA	-47		-48		49 / -		52 / -	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~48							
	Heating	Ambient	Min.~Max.	°CWB	-15 ~18			---				
Refrigerant	Type	R-32										
	GWP	675.0										
	Charge	kg/ tCO2Eq			0.55 / 0.37	0.70 / 0.48		0.90 / 0.61		1.15 / 0.78		
Piping connections	Liquid	OD		mm	6.4							
	Gas	OD		mm	9.5			12.7				
	Piping length	OU - IU	Max.	m	20							
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)							
Power supply	Level difference	IU - OU	Max.	m	12			20				
	Phase/Frequency/Voltage			Hz/V	1~/50 / 220-240							
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20				

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data				FTXP + RXP	20N + 20N	25N + 25N	35N + 35N	50N + 50N	60N + 60N	71N + 71N	
Cooling capacity	Min./Nom./Max.			kW	1.3 / 2.00 / 2.6	1.3 / 2.50 / 3.0	1.3 / 3.50 / 4.0	1.7 / 5.0 / 6.0	1.7 / 6.0 / 7.0	2.3 / 7.1 / 7.3	
Heating capacity	Min./Nom./Max.			kW	1.30 / 2.50 / 3.50	1.30 / 3.00 / 4.00	1.30 / 4.00 / 4.80	1.7 / 6.0 / 7.7	1.7 / 7.0 / 8.0	2.3 / 8.2 / 9.0	
Power input	Cooling	Min./Nom./Max.		kW	0.31 / 0.530 / 0.72	0.31 / 0.660 / 0.72	0.29 / 1.07 / 1.30	0.320 / 1.385 / 1.826	0.332 / 1.824 / 2.980	0.449 / 2.689 / 3.274	
	Heating	Min./Nom./Max.		kW	0.25 / 0.520 / 0.95	0.25 / 0.690 / 0.95	0.29 / 0.990 / 1.29	0.440 / 1.579 / 2.356	0.456 / 1.928 / 2.787	0.617 / 2.571 / 3.306	
Space cooling	Energy efficiency class				A++						
	Capacity	Pdesign		kW	2.00	2.50	3.50	5.0	6.0	7.1	
	SEER				7.20			7.30		6.82	
Space heating (Average climate)	Annual energy consumption			kWh/a	97	121	170	240	308	401	
	Energy efficiency class				A++						
	Capacity	Pdesign		kW	2.20	2.40	2.80	4.60	4.80	6.20	
	SCOP/A				4.65	4.61	4.64	4.40	4.10	4.01	
Nominal efficiency	Annual energy consumption			kWh/a	663	728	845	1,463	1,638	2,166	
	EER				3.75			3.61		3.29	
	COP				4.77	4.36	4.02	3.80	3.63	3.19	
	Annual energy consumption			kWh	-			693		912	
Current - 50Hz	Energy labeling Directive	Cooling/Heating			A/A						
	Maximum fuse amps (MFA)			A	-			20			

Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · www.daikin.eu · BE 0412 120 336 · RPR Oostende



ECPEN23-046 01/2023



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.